

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

UTILITY PATENT APPLICATION

FOR

BIOREACTOR APPARATUS AND CELL CULTURING SYSTEM

BY

JOHN C. VELLINGER

KENNETH W. BARTON

MARK E. WELLS

and

MARK S. DEUSER

"BIOREACTOR APPARATUS AND CELL CULTURING SYSTEM"

This application claims priority from United States Provisional Application Serial No. 60/243,121 filed on October 25, 2000. This application is part of a government project,
5 Contract No. NAS8-98120.

Field of the Invention

The invention relates to the field of a fully-automated perfused cell-culture bioreactor system (laboratory in a cassette).

Description of the Prior Art

10
15
20 There are a number of investigations being conducted on cell growth in specialty bioreactors, which could potentially benefit from use of our device. The research has application in areas as diverse as tissue engineering and transplantation, cancer research and even insect culture and the potential of generating products from cells grown in microgravity. General areas include implantable cartilage tissue grown on artificial scaffolds; cardiac muscle tissue to study drug effects on muscle disease; HIV pathogenesis studies in lymphoid cells; evaluation of renal toxicity; and colon, ovarian, breast, and prostate cancer models.

25 A new discipline in the area of cell culture is emerging. Tissue Engineering is basically the growth of any tissue or organ by applying principles of chemical and physical modifications to the environment, including use of special bioreactors to create three-dimensional cultures. A number of biotechnology companies are currently working on processes in which external forces may be used to control cells and their products and to possibly confer differentiation ability. Tissue modeling, architecture and differentiation depends on the arrangement and
30 juxtapositioning of interacting cells. The gentle environment provided for cell culture in the bioreactor described and

claimed herein should optimize conditions for tissue formation. In conventional bioreactors with stirring devices, the degree to which cell aggregates increase in size depends on the rate of formation and the rate of destruction of the cellular bridges .
5 Principles of tissue engineering in microgravity using the present invention are applicable to regrowth of nerve tissue. Mammalian neuronal precursor cells *in vitro* can make graft therapy a practical approach to the treatment of such neurological diseases as Parkinson's, Alzheimer's and
10 Huntington's disease. The limited availability of transplant tissue seriously limits this type of treatment.

15 In the area of diabetes research, proislet cells prepared from human fetal pancreatic proislets and maintained *in vitro* in the presence of endocrine growth factors (IGF-1) may provide a source of tissue with enriched beta-cell activity and may be suitable as a source of transplantable tissue. For successful transplantation of pancreatic cells, it is necessary to remove the immunogenic cells present in the preparation. Culture of
20 pancreatic preparations in the rotating bioreactors can be a model for determining the presence of immunogenic cells in the cultured pancreatic isolates. In other areas of research utilizing bioreactors, European researchers have characterized cultured yeast cells grown in microgravity in bioreactors and
25 monoclonal antibody production in bioreactor systems as an alternative to production in mice suggests feasibility of using bioreactors instead of mice for antibody production.

30 Cell survival in culture is dependent on the transfer of nutrients and oxygen to the cells and removal of spent metabolites from the local vicinity of cells. For the low-shear mixing, it is necessary to impart a low level of fluid motion to create effective mixing of the fluid in the cell reactor. One of the most important attributes of the rotating-wall reactor technology is the ability to grow cells in a low-shear
35 environment to attain higher cell densities than in conventional

stirred bioreactors. The trade-off is that cell density must be balanced with the ability of the system to supply nutrients and remove spent metabolites while maintaining pH and CO₂ levels within acceptable ranges.

5

SUMMARY OF THE INVENTION

10 A bioreactor apparatus and cell culturing system is provided
for the automated cultivation and processing of living cells
remotely both on earth and in low gravity which utilizes a
generally cylindrical reactor vessel that may be optionally
rotated about its cylindrical axis while allowing the entrance
of fresh or recycled fluid and the removal, optionally, of spent
medium, medium to be recycled or filtered or unfiltered medium
for the collection of samples. The bioreactor vessel a
cylindrical wall, two cover plates, two rotary unions, fill
15 ports, and a polymeric filter. A method of exchanging gases
between the culture medium and ambient gases is fabricated from
a user-selected length of permeable tubing and a peristaltic
pump. A polymeric fresh-medium storage bag and peristaltic pump
is used for batch feeding, perfusion or sample collection. A
sealed compartment for sample-collection bags provides a level
20 of chemical containment for safety. More particularly, an
enclosure and manifold representing an additional level of
chemical containment and a series of pinch valves for the
periodic collection of samples of suspended cells or cell-free
medium is disposed therein together with a humidity control
25 system consisting of a polymeric porous matrix and a fan. A
computer program with graphical user interface for automatically
and/or robotically controlling all functions especially including
rotation of the reactor vessel, feeding fresh medium, perfusing
the reactor vessel, timed collection samples of fluid from the
30 reactor, selecting between collecting cells or cell-free
supernatant. A sealed external housing is used for all
components of the device except the power supply and computer.
All polymeric components are made of low-flammability, non-toxic,

heat-resistant polymers such as polycarbonate, polysulfone, polypropylene, polytetrafluoroethylene, or silicone.

5 The bioreactor apparatus and cell culturing system preferably includes a rotary multiple sample collector with capability for collecting cells on filters, fixing the cells and collecting the cells.

10 The rotary sample collector includes a rotating inlet into a compartment with a filter, means to remove waste liquid from an input cell suspension, means for collecting cells in chambers in liquid suspension, and means to store fixed cells for later recovery and examination.

15 The bioreactor and cell culturing system of the present invention provides many advantages over conventional bioreactors. The features include, but are not limited to, options for gentle mixing of cell and/or microcarrier suspensions (rotation of vessel and/or impeller), independently variable perfusion and oxygenation rates, pH and oxygen monitoring, real-time imaging of cells in an external loop, compact design, computerized and automated control of all functions, user-friendly access and operation, and flexible options for automated collection of samples of cells and/or cell-free media during each experiment. The instant bioreactor will fit conveniently into a cassette with a volume less than 2.0 L (space-flight version) or on a single shelf of a standard tissue culture incubator.

20 The bioreactor of the present invention includes dual channel lower fluid unions, a low-pressure-drop filter which utilizes novel methods to prevent cell capture on the filter .

30 A video camera system integrates a miniature camera, stopped-flow microscopic observation slide, and LED backlighting optics.

The device incorporates analytical sensors to measure pH and oxygen. The novel rotary cell sample collector utilizes an upper and lower collector plate, a drive mechanism to rotate the

upper plate, and utilizes sample collection syringes. The system further includes the cell growth reactor, rotary cell sample collector, CCD camera, sensors, and the peristaltic pump. Table 1 sets forth the general parameters of a preferred embodiment as follows:

Cell Growth Reactor	CCD Camera System
Sample Volume- 50 ml Rate of Rotation- 6 RPM (uniform rotation) Upper Rotary Union- 1 inlet Lower Rotary Union- 2 independent outlets for: 1. Medium Only (Cells are filtered) 2. Medium and Cells Capability To Add Medium Upon Demand Transport Viewing Surface for Video Observations Oxygenation of the Medium in the Reactor Sample Port for Loading and Unloading Reactor Materials Compatible with Cell Growth	Video Frame Grabber: 1 frame per 30 seconds Beam Splitter for Dual Optical Viewing of: 1. Cell Growth Reactor 2. Microscopic Observation Slide Optimal LED Backlights
	Sensor System
	Continuous measurement of pH 1. Ability to autoclave/disinfect electrodes 2. Monitor pH level range of 6.5 to 7.5 Glucose Monitoring
Miniature Peristaltic Pump	Rotary Cell Sample Collector
Deliver Medium Solution to Cell Growth Reactor Circulate Medium Into/Out-of Cell Growth Reactor	Collect Fixed Cell: 6-8 samples Collect Medium: 6-8 samples

Table 1. Hardware Requirements and Specifications, Subsystems

The bioreactor cassette fluid unions provide the capacity to add growth medium, to extract spent medium, to collect cell samples.

The instant bioreactor also provides three fluid flow paths, the feed cell flow path, sample collection flow path, and aeration flow path. The fluid flow path delivers medium from the storage bag to the bioreactor when the cells need nourishment or when a medium sample is collected. The sample collection flow path delivers medium from the bioreactor to sample collection bags or cuvettes. The aeration flow path circulates the medium through the silicone tubing in an ambient or oxygen enriched environment whereby oxygen passes through the tubing oxygenating the medium.

The present invention utilizes pinch valves between the

sample containers, waste container, and a sample manifold in order to isolate samples.

5 An advantage of the present invention as compared to conventional bioreactors is that the system allows samples of both filtered (no cells) and unfiltered (with cells or particles) media to be extracted automatically during bioreactor operation. Cell filtration takes place internal to the reactor. Both cell and media sample extraction take place thorough the concentric nested exists into the lower rotary fluid union.

10 The instant bioreactor provides a large filtration area with respect to the small bioreactor size. This feature minimizes both the pressure drop across the filter, (and in turn the system working pressure), and the fluid velocity through the filter (minizing cell attachment and clogging of the filter).

15 The instant bioreactor hub design is unique in that the central rotation hub encompasses more than one fluid outlet. The hub also contains the filter support surface. The design is simple and has a miminal parts count. The hub provides alignment for the bioreactor component stack which includes the lower fluid union, hub, filter, spacer, upper cover, and upper fluid union.

20 Moreover, the present invention incorporates the bioreactor into a system utilizing a rotation drive and perfusion pump, sampling system, and pressure relief system. The system provides a means for cell sampling, dilution, and fixation.

25 The valve design allows the distribution valve to utilize pinch valve features without using multiple pinch valves to minimize the use of serialized tubing (serialized tubing versus having to sterilize the valve as is often required with conventional systems).

It is an object of the present invention to include the following features: a cell chamber volume, perfused system, zero head space, variable temperature control, teleoperation as an option, 1G centrifuge adaptable, oxygenation capability, capable of utilizing microcarriers, capable of maintaining long term cultures, multiple individual sample containers, interval sampling capability, fixation at selected times, filtration of cells from medium, automated delivery of fixative, sample storage of between 4 and 20 degrees centigrade, physiological sensors for pH, glucose, oxygen, etc., addition of activators to culture chambers, and the ability to be automated and self contained.

It is an object of the present invention to provide a flow-through bioreactor whereby the interior surfaces of the bioreactor's fluid volume are smooth to minimize the likelihood of cell attachment.

It is an object of the present invention to provide a temperature control system capable of controlling the temperature from -4°C to 38°C and preferably at about 37°C.

It is an object of the present invention to provide a sample collection capability of one or more independent samples.

It is an object of the present invention to provide a means of collecting different types of cells or to collect only cells or particles, only media, or both.

It is an object of the present invention to provide a capability to separate cells from culture medium for sampling.

It is an object of the present invention to provide a medium which is replenishable by means of perfusion which is programmable or active on demand.

It is an object of the present invention to provide a medium for continuous oxygenation.

It is an object of the present invention to provide a means of gently mixing of cell and or particles in the medium by rotation or impeller.

It is an object of the present invention to provide as an option a circulation fan to maintain uniform gas exchange and thermal control.

It is an object of the present invention to provide a means for humidity control.

It is an object of the present invention to provide a means of providing the apparatus in a modular cassette in order to facilitate sequential and/or parallel experiments.

It is an object of the present invention to provide a means for the researcher to have experiment flexibility and select solutions, temperatures, and sampling times.

It is an object of the present invention to provide a means for collecting samples of cells, particles, or medium in bags, cuvettes, syringes, or other vessels.

It is an object of the invention to provide means for disassembling the cell growth reactor for autoclaving.

It is an object of the present invention to provide a bioreactor cell culturing system designed to be utilized in a cassette integrated within a space flight processing facility.

These and other objects of the present invention will be

more fully understood from the following description of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

5 A better understanding of the present invention will be had upon reference to the following description in conjunction with the accompanying drawings in which like numerals refer to like parts throughout the several views and wherein:

Figure 1 is an exploded view showing the components of a preferred embodiment of the bioreactor vessel;

10 Figure 2 is an elevational side view of the present invention showing the assembled bioreactor vessel of Figure 1;

Figure 3 is a cross sectional view of the present invention along lines 3-3 of the reactor vessel of Figure 1 showing the seals and components assembly;

15 Figure 4 is a plan view showing a sealed container of the present invention for sample collection bags and the positioning of pinch valves;

Figure 5 is a schematic diagram of the present invention showing a fluid handling subsystem flow path;

20 Figure 6 is a plan view of the bioreactor of the present invention and automated cell cultivation and processing cassette unit;

Figure 7 is a flow diagram of the present invention showing the sequence for the rotary cell sample collector;

Figure 8 is a flow diagram of the present invention showing the fluid flow path for the sample collection;

Figure 9 is a flow diagram of the present invention showing the flow path of the fluid and cells through the bioreactor, photo system, together with the media supply bag and sample collection and waste containers;

Figure 10 is a top view of a photo device for the present invention for viewing the cells in suspension in macro or micro view;

Figure 11 is a perspective view of a microscopic observation slide developed for the photo system of the present invention showing the slide endcaps for attaching to the tubing from the rotary cell reactor and the rotary cell sample collector;

Figure 12 is a perspective view showing the lower plate of the rotary cell sample collection held stationary while the upper plate is rotated by the stepping motor;

Figure 13 is a diagram depicting the sample collection syringes mounted to the lower plate;

Figure 14 is a perspective view of a miniature peristaltic pump developed for the present invention;

Figure 15 is a perspective cutaway view showing a cassette within a containment enclosure comprising a cassette assembly for insertion into a middeck locker processing facility; and

Figure 16 is a perspective cutaway view showing a middeck locker processing facility.

DESCRIPTION OF THE PREFERRED EMBODIMENT

A device for the Automated Cultivation and Processing of Living Cells Remotely and in Low Gravity is generally designated 100 in the drawings. As set forth in the drawings, the individual components of the device 100 will first be identified and the operation of, and fluid flow through, device 100 will then be described.

The cultivation and processing device includes a reactor vessel 20, which, as shown in detail in Figure 1 consists of cylindrical wall 6 affixed to an upper cover 11 and lower cover 5 to which it is sealed by stationary O-rings 8. The upper cover plate is perforated by two fill ports 13 with relief-valve covers 14 and by a bearing hole for the tubular axle that is one piece with lower plate 5, which axle is capped at the top plate by upstream rotary union 19 and by bispout 4. The lower cover plate 5 supports a polymeric filter 7, which prevents cells from exiting the reactor when fluid is withdrawn through the upper one bispout of two bispouts 4 attached to downstream rotary union 1, which is sealed to the lower cover plate by O-rings 2 and 3. Cell-containing fluid is withdrawn through the lower one bispout of two bispouts 4 under the control of valves and pumps to be described in Figure 5. The cylindrical wall, top cover plate and lower plate are secured together by machine screws 17 to assemble the reactor vessel as shown in Figures. 2 and 3.

When samples are withdrawn for later study, fluid is pumped into one of more or less than six partially evacuated sample bags 35, which are housed in a sealed compartment 30 shown in Figure 4. The bags 35 in sealed compartment 30 may contain formaldehyde fixing solution or RNA extracting solution or a solution of any reagent or any solid reagent with which the experimenter wishes the withdrawn sample to react. Therefore, sealed compartment 30 represents a third level of containment in the embodiment of the

device 100 shown in Figure 6 and allows the housing of solutions of Hazard Level 2 therein. Withdrawn samples enter the bags 35 in the sealed compartment 30 through tubing connectors 32 that perforate, manifold-style, one wall of sealed compartment 30.

5 The functioning of the device for the Automated Cultivation and Processing of Living Cells is best understood using the flow diagram in Figure 5 of the drawings. A suspension of cells or cells attached to microcarrier particles or three-dimensional tissue or other planktonic organisms is maintained in a (usually, but not necessarily, nutrient) liquid medium in reactor vessel 10 20 as the primary goal of the Device. Feed liquid medium is stored in medium storage bag 42, which is connected to medium feedline 46 by barbed fitting 44. Medium is drawn through this line by peristaltic pump 48 and passed on to the reactor via T-fitting 54 and spout 4, which admits medium into the upstream rotary union 19 and the culture vessel 20. The bursting of the flexible tubing of feed line 46 and recirculation line 56 is prevented by pressure relief valves 50 that will shunt liquid directly to waste storage bag 66 in the event of an overpressure. At user's option peristaltic pump 55 may be used to pump medium through external loop 56, which may consist of gas-permeable tubing of various lengths up to approximately 1 m for exchange between gas dissolved in the medium and ambient gas or may serve a sensor (not shown) of the composition of the medium. The 25 direction of flow through external loop 56 indicated by a curved arrow. To operate the reactor in continuous perfusion mode or in batch-fed mode peristaltic pump 48 supplies fresh fluid through rotary union 19 into the vessel, from which spent medium exits through rotary union 1 into exit lines 58 and 60, through open pinch valve 64 and into waste storage bag 66. For the 30 collection of samples, one of the six solenoid pinch valves 62 is opened, peristaltic pump 55 is off, and peristaltic pump 48 operates to provide driving pressure and make-up volume for sample fluid.

35 The volume of the medium storage bag is 100 mL, that of the

reactor vessel is 50 mL, and the volume of the waste storage bag is 100 mL in one possible embodiment. Typical volume of sample collection bags is 6 mL each, more or less.

5 An embodiment of the Device, designed for cultivating cells automatically in space flight, is shown in Figure 6 of the drawings. In addition to the components just described, a motor 72 is used, with a gearing mechanism 74 to drive belt 76, which causes reactor vessel 20 to rotate on its axis supported by yoke 78. Tubing is not shown. A water-saturated polymeric porous
10 medium (sponge) 80 may be used to maintain humidity in the sealed housing 70, which provides one level of chemical containment for safety.

In all embodiments, a computer controls the functions of all energized parts, namely peristaltic pumps 48 and 55, solenoid pinch valves 62 and 64, humidification fan at 80 (not shown), and drive motor 72. A computer program with a Graphical User Interface (GUI) allows the user to sequence the events within the Device over periods of several days to weeks.

Application and Experimental Method

20 The 50 ml polycarbonate cell growth reactor as best shown in Figures 1-3, is the heart of the system, since it supports the growth and viability of the cells during an experiment. The interior surfaces of the cell growth reactor are smooth to eliminate any cell entrapment points while, in addition, the
25 reactor is capable of rotating at rates up to 6 RPM to keep the cells in suspension. The rotation of the cell growth reactor is accomplished by using a timing belt wrapped around the reactor that is driven by a DC motor, which also drives the peristaltic pump head.

30 The cell growth reactor is optically transparent on the

upper surface to permit video observations of the internal contents. The reactor also has several fill and extraction locations on the outside of the vessel. One side port and two top ports simplify the sample loading and unloading process for each experiment. The prototype units fabricated to date contain two fluid unions. One fluid union is located at the top of the reactor while the other fluid union is located at the bottom of the reactor. The rotary fluid unions allow the entry and removal of the medium solution with or without the cells while the reactor is rotating.

The upper rotary union is a single-pass channel that permits fresh medium to be delivered to the cell growth reactor while the lower rotary union has two independent exit channels. The fluid flow block diagram is shown best in Figures 5 and 9. The channels in the lower rotary union allow either filtered or unfiltered medium to pass out of the cell growth reactor. The filtered medium does not carry any cells within the solution while the unfiltered medium contains live cells. The filtered medium is used for oxygenation of the cell growth reactor by passing solution through 60-cm of thin-walled silicone tubing which is exposed to an ambient or oxygen enriched environment. In addition, the filtered medium passes over the sensors which provide pH and dissolved oxygen (DO) measurements. However, it is contemplated that samples could be collected and analyzed for pH, glucose, and dissolved oxygen. The unfiltered medium passes through the microscopic observation slide and on to the rotary cell sample collector.

The video concept provides observation capability of the bioreactor as well as microscopic observation of individual cells. Due to the space constraints within the space-flight cassette, both miniaturization and optimization of this system comprises a significant innovation. The entire camera and microscope system must fit within a volume of approximately 4x2x10 centimeters.

The camera illustrated in Figure 10 utilizes a dual optical path configuration and a single ½ inch color CCD camera or video plane for both optical systems. One optical path will allow observation of the rotating cell growth reactor contents with a 20 x 25mm Field Of View (FOV). The other microscopic observation path will provide a 4 x 5mm FOV with approximately 5-micron resolution of cell samples that have been extracted from the bioreactor and pumped into the observation cell (see below). The candidate resolution for the microscopic system is based on a 12-micron pixel size.

A digital camera and/or video device could be used to show instantaneous or still frame pictures. The ELMO camera system in this embodiment has a remote miniature camera head, which contains the CCD and a separate controller. The controller is located outside of the space-flight cassette. The camera head is attached to housing containing a 12.5mm beamsplitter cube. One side of the beamsplitter is attached to an objective lens, which views one side of the bioreactor volume through a turning prism. The prism is enclosed to prevent contamination of the Total Internal Reflection (TIR) surface. The viewing surface of the prism can be heated slightly using a Minco (or equivalent) foil type heater to prevent condensation (the interior of the cassette is maintained at high relative humidity). The other side of the beamsplitter is attached to a spacer barrel, which is attached to the microscopic observation slide. The spacer tube provides the path length required between the CCD and the objective lens to achieve the desired magnification or FOV. The space between the objective lens and the observation cell surface is sealed and back-filled with dry nitrogen to prevent condensation. Other air spaces within the video system optics is sealed and backfilled with dry nitrogen.

Connection between the camera cable from the camera head in the cassette and the external camera controller is made using a separate connector in the housing of the cassette. Camera images are stored digitally using a frame grabber PC104 board in

the precessing facility shown in Figure 16. Image capture is controlled by a programmed routine. The current candidate frame grabber PC104 board is from Image Nation.

5 A modular slide system that is utilized for each observation application has been developed. Slide material selection is critical in slide development (see Figure 11). Glass, polycarbonate, and various other materials are interchangeable depending upon the physical requirements and environments of operation of the unit.. The superior optical clarity,
10 biocompatability, chemical compatibility, low cost, and ready availability of glass made it the preferred choice for the microscopic observation slide. The only shortfall of glass is that it is a shatterable material and would pose several design issues for space flight applications.

15 The LEDs utilized in this hardware will be responsible for providing uniform light to the cell growth reactor as well as the microscopic observation slide. From our examination of the spectral distribution of the LEDs required for video observations of the cells, it has been determined that only white light is required; however, radiation of other wavelengths may be utilized for particular applications. LEDs are available that are able to meet the spectral distribution of 430 to 690 nm. The other advantages of LEDs are the reliability and the low thermal impact on the overall system without the EMI and containment issues
20 associated with fluorescence. LEDs are now available with spectral distribution curves that approximate white light. Of course, means of lighting such as conventional types of light emitting devices may be utilized especially in earth applications wherein the energy and weight considerations are of less
25 importance as compared to the cost savings.
30

Selection of the camera view between the cell growth reactor and the microscopic observation slide is made by turning on or off the appropriate light source. To observe the cells in the

microscopic observation slide, the reactor light is turned off and the microscopic slide backlight is turned on. The microscopic observation slide is backlighted using a single LED and a diffuser. Backlighting is not possible for the bioreactor due to its design. The bioreactor, therefore, is illuminated by selection of two LEDs providing front lighting or two LED's providing oblique lighting. This approach allows the camera to see the image from the reactor.

A novel rotary cell sample collector for space-flight applications (see Figure 12) provides the capability to collect and fix cell samples upon demand via telemetry or pre-programmed timelines. The rotary cell sample collector utilizes two plates clamped together at their centers and sealed with a grease such as vacuum grease or other low solubility and low vapor pressure grease such as a silicone grease.. The lower plate remains stationary while the upper plate is rotated by the stepping motor. The upper plate is rotated by a two-phase flight-proven stepping motor that provides precise control for proper alignment. The cells and medium exit the reactor vessel at the lower rotary union on the unfiltered side after additional medium is added upstream to the cell growth reactor. Then, the cells and medium pass through the microscopic observation slide, and then on to the rotary cell sample collector.

The cells and medium enter the rotary cell sample collector upper plate at one location via a threaded hose barb (see Figure 13). In order to avoid the use of fluid unions, the upper plate is only permitted to rotate 360° to prevent the inlet line from becoming unattached or twisted. The single inlet located in the upper plate delivers the cells and medium directly to a pair of collection syringes mounted on the lower plate. Collection in syringes (cylinders with movable pistons) has been chosen over collection in bags. Of course it is contemplated the cuvettes or other collection containers may be utilized as well. One sample syringe is used to collect the medium while the other syringe contains fixative used to preserve the cells such as

formaldehyde or other chemical reagent. A pinch valve is opened, and the medium is forced into the collection syringe. Once the medium has been collected, the pinch valve for the fixative is opened, and fixative is forced over the cells. This technique lifts the cells off the filter to provide optimal cell fixation. Both syringes are easily removed to provide convenient access to the samples following an experiment.

One of the main technical challenges is to provide the capability to flush the feed lines and be guaranteed fresh medium and live cells enter the cell collection syringe. In order to flush the line before sample collection, the upper plate is aligned over a waste hole in the lower plate. The hole is plumbed directly to the waste bag located downstream from the rotary cell sample collector. Therefore, before a sample is collected, the upper plate is aligned over a through hole and the line is flushed free of any dead cells or spent medium. When it is time to collect a sample (See Figure 7), the lines are flushed out and then the upper plate is rotated over to the next set of sample collection syringes. First, the pinch valve is opened for the medium collection. The cells and medium are pumped into the chamber. A layer of filter material prevents the cells from entering into the medium collection syringe. After the medium has been collected into the syringe, the pinch valve is closed. Next, the pinch valve for the cell fixative is opened. The pressure generated by the compressed spring pushes the plunger up and the fixative lifts the cells off the filter material. To equalize the pressure, the cells flow into the backside of the fixative syringe. After the sample is collected, the upper plate is rotated to the next opening, which allows cells and medium to be passed through the microscopic observation slide, if desired, and on to the waste bag. This flow path can be activated multiple times until it is time to collect another sample.

More particularly, as illustrated in Figure 7 the sequence for the rotary cell sample collector is as follows:

a) Position of the collection syringes before a sample is collected;

b) The pinch valve for the sample of medium and cells is opened, the cells remain on the filter material while the medium pushes the syringe plunger down, and the pinch valve is closed;

c) The pinch valve for the fixative syringe is opened, and the fixative flow lifts the cells off the filter material, and the pressure forces the liquid to the backside of the syringe.

It is important that the system incorporate means to determine the optimal technique for delivering multiple fluids to multiple locations. A peristaltic pump as best illustrated in Figure 14 was designed to fit the present application. In preference over stepper motors and micro pumps a conceptual design for a new miniature peristaltic pump was developed. The pump was designed so it could deliver controlled amounts of growth medium as well as circulate medium in and out of the cell growth reactor for oxygenation. The fluid system was designed with pinch valves located upstream of the miniature peristaltic pump to prevent the liquid from flowing through the pump except when the valves are open.

The miniature peristaltic pump has the capability to deliver precise amounts of medium into the cell growth reactor. The pump can deliver quantities as small as 0.015 cc. This type of precision is extremely critical for the overall operation of the system because pumping new growth medium into the cell growth reactor also pumps medium with live cells into the microscopic observation slide and the rotary cell sample collector.

The present invention can be fabricated as a stand alone instrument or incorporated into a family of cassette that includes a unit within a processing facility (see Figure 16). This family of units consists of modules or cassettes as shown in Figure 15, all of which are designed for accommodation in and control by BIOTEC. a fully automated, multi-use bioprocessing

thermal environment controller for the processing of biological samples in space or utilized in earth laboratories. It is a single-locker facility designed for accommodation in the Shuttle Middeck, Spacehab locker, and/or Space Station EXPRESS rack. This modular system facilitates a range of biotechnology processes all of which are applicable to earth research and development.

The BIOTEC flight processing facility contains independently controlled processing modules or cassettes that can either be programmed for totally automated operation, or controlled via telemetry for real-time telescience and telerobotic operation. The processing temperature can be independently controlled and regulated between 4-40°C in each of the processing modules. Biological samples for processing are loaded (preflight, on the ground) into specially designed containers, which are housed within a compact cassette that provides an appropriate level of containment for processing in the processing facility.

The instant bioreactor, when utilized in a cassette will be designed to operate within the space-flight instrument referred to as a BIOTEC facility consisting of a group of identical spaceborne processing modules designed to accommodate a family of cassettes having identical envelopes. Each cassette accommodates a specific type of biotechnology experiment, such as crystallization, separations or cell cultivation. Each cassette interfaces with the BIOTEC computer and power via a smart multi-pin connector, and the BIOTEC processing module responds automatically with a sequenced experiment protocol for each cassette.

The foregoing detailed description is given primarily for clearness of understanding and no unnecessary limitations are to be understood therefrom, for modification will become obvious to those skilled in the art upon reading this disclosure and may be

made upon departing from the spirit of the invention and scope of the appended claims. Accordingly, this invention is not intended to be limited by the specific exemplifications presented hereinabove. Rather, what is intended to be covered is within
5 the spirit and scope of the appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235